

PERFORMA™

Directional Fissured



LEED®

- ✓ Optimize Energy Performance
- ✓ Construction Waste Management
- ✓ Recycled Content
- ✓ Regional Materials
- ✓ Sustainably Sourced Materials and Products
- ✓ IEQ: Low-Emitting

RECYCLED CONTENT

CLASS A

18% Pre-consumer | **17%** Post-consumer

PROTECTONE®

37% Pre-consumer | **8%** Post-consumer

RELATIVE INSTALLED COST: \$\$\$\$

FEATURES & BENEFITS

- Economical directional fissured pattern
- Third-party verified Environmental Product Declaration (EPD) available for this product
- Available in fire-rated (Protectone®) versions
- No added formaldehyde

APPLICATIONS

- Utility Areas
- Discount Areas
- Strip Malls
- Commercial Interior Spaces

AVAILABLE EDGE DETAILS



Trim
15/16" Grid



ATTRIBUTES

ITEM NUMBER	DIMENSIONS (INCHES)	EDGE DETAIL	UL CLASSIFIED		SAG RESISTANT	MOLD RESISTANT	LR	WASHABLE	SCRATCH RESISTANT	FIRE RATING	EMISSIONS	RECYCLED CONTENT
			NRC	CAC								
FH-157	24 x 24 x 5/8	Trim	0.60	33	—	—	0.82	—	—	Class A	Certified	35%
PFH-157	24 x 24 x 5/8	Trim	0.55	35	—	—	0.82	—	—	Protectone*	Certified	45%
FH-197	24 x 48 x 5/8	Trim	0.60	35	—	—	0.82	—	—	Class A	Certified	35%
PFH-197	24 x 48 x 5/8	Trim	0.55	40	—	—	0.82	—	—	Protectone*	Certified	45%

Protectone: A fire-resistive ceiling when used in applicable UL assemblies.

PHYSICAL DATA

MATERIAL

Mineral Fiber

ASTM E1264 CLASSIFICATION

Type III, Form 2, Pattern C D

FIRE PERFORMANCE

Per ASTM E1264: Class A, Flame Spread 25 or less
Per ASTM E84: Smoke Developed 50 or less

VOC EMISSIONS

Independently certified compliant with California
Department of Public Health CDPH/EHLB/Standard
Method Version 1.1, 2010.

MOLD/MILDEW RESISTANCE

BioShield™ treatment included for added mold and
mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

1 year Warranty