



## Style Specifications – Contour Series

All floors shown or listed in this specification shall be Contour Series by Centiva, Florence, AL, 35630.

Specific product shall be: \_\_\_ \_\_\_ C \_\_\_ \_\_\_ in size \_\_\_" x \_\_\_"  
Style Color Series Surface Edge

The Centiva Contour Series shall be constructed with a .032" high density wearlayer. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each line. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 WET SET, CENTI 2000 EP, or CENTI 6000 SP. Installation shall be in accordance with the latest Centiva Installation Guidelines found at [www.centiva.com](http://www.centiva.com).

*The Contour Series square tiles are recommended to be installed using the one-quarter turn installation method for best design appeal and results. Rectangular shaped tiles should be installed in one direction.*

## CONTOUR SERIES – FESTIVAL

### ADAGIO

FE 0785-C Adagio Blue

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 18" x 18", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
<b>Standard Colors:</b>	1 color		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## ASPHALT

FE 0721-C Asphalt    FE 0722-C Arizona Asphalt

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	18" x 18" (only)		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU)		
<b>Standard Colors:</b>	2 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## BETON

FE 7220-C Dune    FE 7221-C Thunder    FE 7222-C Cloud  
FE 7223-C Meadow    FE 7224-C Clay    FE 7225-C Terracotta

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36", 4" x 36", 6" x 36" plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU)		
<b>Standard Colors:</b>	6 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## CONCRETE II

FE 7303-C Concrete II Gray    FE 7305-C Concrete II Brick    FE 7307-C Concrete II Tan

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	18" x 18", 12" x 36", 18" x 36", 36" x 36", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Quarry (QU) <i>recommended</i> , Fresco (FC), Frost (FR), Pathway (PH)		
<b>Standard Colors:</b>	3 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product



## SIGMA

FE 0745-C Pure      FE 0747-C Phantom      FE 0749-C Nature

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 18" x 18", 4" x 36", 6" x 36" plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
<b>Standard Colors:</b>	3 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## TIDE

FE 0701-C Night Tide      FE 0705-C Dusk Tide      FE 0707-C Evening Tide

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36", 4" x 36", 6" x 36" plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
<b>Standard Colors:</b>	3 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## WEAVE

FE 0711-C Greenweave

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	18" x 18" (only)		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Frost (FR) <i>recommended</i> , Fresco (FC), Pathway (PH), Quarry (QU)		
<b>Standard Colors:</b>	1 color		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product



## CONTOUR SERIES – STONE

### AEGEAN

CS 0501-C Aegean Sea

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12" (only)		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Quarry (QU) <i>recommended</i> , Fresco (FC), Frost (FR), Pathway (PH)		
<b>Standard Colors:</b>	1 color		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

### ANCIENT STONE

CS 0531-C Parthenon Gold    CS 0562-C Alcantara

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 18" x 18", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU)		
<b>Standard Colors:</b>	2 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

### ARCADIAN

CS 0541-C Arcadian Pilar    CS 0542-C Arcadian Column    CS 0554-C Arcadian Arch

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 18" x 18", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Quarry (QU) <i>recommended</i> , Fresco (FC), Frost (FR), Pathway (PH)		
<b>Standard Colors:</b>	3 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

## ATLANTIS

CS 0521-C Atlantis Bone    CS 0522-C Atlantis Beige    CS 0523-C Atlantis Metal  
CS 7241-C Atlantis Brown    CS 7242-C Atlantis Blue    CS 7243-C Atlantis Gray

**Classification:** ASTM F 1700 Class III Solid Vinyl Tile  
**Construction:** Multiple layers with backing which contains pre- and post-consumer material  
**Overall Thickness:** .120" / 3 mm (nominal)  
**Wearlayer Thickness:** .032" clear, rigid high density PVC  
**Size:** 12" x 12", 12" x 18", 18" x 18", 12" x 36", 18" x 36", 36" x 36" plus additional custom sizes  
**Edge:** Square, Slight Bevel  
**Surface Texture:** Quarry (QU) *recommended for Atlantis Beige, Bone, & Metal*, Fresco (FC) *recommended for Atlantis Brown, Gray, & Blue*, Frost (FR), Pathway (PH)  
**Standard Colors:** 6 colors  
**Warranty:** 20 years Commercial, Lifetime Residential  
**Recycling:** Suitable  
**Test Performance:** ASTM E 648    Critical Radiant Flux    Class I CRF>0.45  
ASTM E 662    Smoke Density    <450; Good  
ASTM F 925    Chemical Resistance    Excellent  
Slip Resistance    ASTM C 1028\*    Very Good (\*textures)  
ASTM D 2047    Passes  
ADA Compliant    FTC Slip Resistant Classified Product

## CLASSICO

CS 0511-C Classico Grey    CS 0513-C Classico Carmel    CS 0515-C Classico Verde

**Classification:** ASTM F 1700 Class III Solid Vinyl Tile  
**Construction:** Multiple layers with backing which contains pre- and post-consumer material  
**Overall Thickness:** .120" / 3 mm (nominal)  
**Wearlayer Thickness:** .032" clear, rigid high density PVC  
**Size:** 12" x 12", 18" x 18", plus additional custom sizes  
**Edge:** Square, Slight Bevel  
**Surface Texture:** Frost (FR) *recommended*, Fresco (FC), Pathway (PH), Quarry (QU)  
**Standard Colors:** 3 colors  
**Warranty:** 20 years Commercial, Lifetime Residential  
**Recycling:** Suitable  
**Test Performance:** ASTM E 648    Critical Radiant Flux    Class I CRF>0.45  
ASTM E 662    Smoke Density    <450; Good  
ASTM F 925    Chemical Resistance    Excellent  
Slip Resistance    ASTM C 1028\*    Very Good (\*textures)  
ASTM D 2047    Passes  
ADA Compliant    FTC Slip Resistant Classified Product

## MODERN LIME

CS 0602-C Lagos    CS 0604-C Porto    CS 0606-C Mocha    CS 0608-C Branco    CS 0610-C Valleta  
CS 0612-C Camino    CS 0614-C Calypso    CS 0616-C Costa    CS 0618-C Volga    CS 0620-C Niko

**Classification:** ASTM F 1700 Class III Solid Vinyl Tile  
**Construction:** Multiple layers with backing which contains pre- and post-consumer material  
**Overall Thickness:** .120" / 3 mm (nominal)  
**Wearlayer Thickness:** .032" clear, rigid high density PVC  
**Size:** 12" x 12", 18" x 18", 36" x 36", plus additional custom sizes  
**Edge:** Square, Slight Bevel  
**Surface Texture:** Quarry (QU) *recommended*, Fresco (FC), Frost (FR), Pathway (PH)  
**Standard Colors:** 10 colors  
**Warranty:** 20 years Commercial, Lifetime Residential  
**Recycling:** Suitable  
**Test Performance:** ASTM E 648    Critical Radiant Flux    Class I CRF>0.45  
ASTM E 662    Smoke Density    <450; Good  
ASTM F 925    Chemical Resistance    Excellent  
Slip Resistance    ASTM C 1028\*    Very Good (\*textures)  
ASTM D 2047    Passes  
ADA Compliant    FTC Slip Resistant Classified Product

## Style Specifications – Contour Series



### PORTOKALI

CS 0561-C Portokali

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 18" x 18", plus additional sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Fresco (FC) <i>recommended</i> , Quarry (QU), Frost (FR), Pathway (PH)		
<b>Standard Colors:</b>	1 color		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

### SANTORINI

CS 0551-C Santorini Kafe    CS 0553-C Santorini Tandem    CS 0557-C Santorini Argos

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	12" x 12", 18" x 18", plus additional custom sizes		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Pathway (PH) <i>recommended</i> , Fresco (FC), Frost (FR), Quarry (QU)		
<b>Standard Colors:</b>	3 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good(*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product



## CONTOUR SERIES – WOOD

### BLOCKWOOD CP 1201-C Caramel Blockwood CP 1202-C Auburn Blockwood

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	36" x 36" (only)		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Quarry (QU) <i>recommended</i> , Frost (FR)		
<b>Standard Colors:</b>	2 colors		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product

### CONTOUR PLANK

CP 3104-C Atlantic Cherry	CP 3105-C Aged Cherry	CP 3106-C Bergerac Beech
CP 3201-C Grappa Noce	CP 3205-C Kingwood	CP 3207-C Bolivian Rosewood
CP 3210-C Brazilian Cherry	CP 3213-C Trio Walnut	CP 3214-C Camphor Wood
CP 3206-C Merrill Birch	CP 3306-C Canadian Maple	CP 3310-C Queensland Walnut
CP 3311-C Hawaiian Teak	CP 3312-C Golden Teak	CP 3324-C Washed Teak
CP 3313-C Golden Rosewood	CP 0305-C Vintage Tower	CP 0303-C Vintage Chalet
CP 0301-C Vintage Lodge	CP 0302-C Vintage Cabin	CP 0306-C Vintage Inn
CP 0311-C Summer Savannah	CP 0321-C High Forest	CP 0333-C English Flat
CP 3302-C Fruitwood	CP 3301-C Zebrano	CP 3314-C Brown Strata
CP 3316-C Olive Strata	CP 3322-C Pale Strata	CP 0355-C Pacific Lighthouse
CP 0357-C Driftwood	CP 0359-C Rustic Cedar	CP 0351-C Pacific Boathouse
CP 0353-C Pacific Shorehouse	CP 3510-C Metallic Green	CP 3511-C Metallic Gray
CP 3512-C Metallic Black	CP 0361-C Newborn	CP 0383-C Wild Bohemian
CP 0381-C Wild BosaNova	CP 3320-C Strand Bamboo	CP 7316-C Ashen
CP 7314-C Carbon	CP 7312-C Barrel	CP 7310-C Moso
CP 3625-C Crestwood	CP 3623-C Foxwood	CP 3621-C Country Manor
CP 3612-C Redwood	CP 3610-C Branch	CP 3608-C Raven
CP 3606-C Willow	CP 3604-C Whisper	CP 3602-C Thistle

<b>Classification:</b>	ASTM F 1700 Class III Solid Vinyl Tile		
<b>Construction:</b>	Multiple layers with backing which contains pre- and post-consumer material		
<b>Overall Thickness:</b>	.120" / 3 mm (nominal)		
<b>Wearlayer Thickness:</b>	.032" clear, rigid high density PVC		
<b>Size:</b>	3" x 36", 4" x 36", 6" x 36", or 7.2" x 48"		
<b>Edge:</b>	Square, Slight Bevel		
<b>Surface Texture:</b>	Frost (FR), Natural Grain (NG), Rough (RG), Sawn (SW), Tick (TK)		
	Recommended surface for each product is shown on sample in sample book		
<b>Standard Colors:</b>	41		
<b>Warranty:</b>	20 years Commercial, Lifetime Residential		
<b>Recycling:</b>	Suitable		
<b>Test Performance:</b>	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450; Good
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ASTM C 1028*	Very Good (*textures)
		ASTM D 2047	Passes
		ADA Compliant	FTC Slip Resistant Classified Product