Sandrift[™] ClimaPlus[™]











Sandrift Panels with *ClimaPlus* Superior Performance/ Donn DX/DXL Suspension System

See LEED report tool at **usgdesignstudio.com** for detailed sustainability information.

Features and Benefits

- Uniquely textured cast product with durable surface that resists scrapes commonly caused by accessing the ceiling plenum.
- Integral color masks nicks and scratches.
- Optional Firecode[®] product designed to meet life-safety codes.
- ClimaPlus 30-year lifetime system warranty against visible sag, mold and mildew.
- USDA Certified Biobased Product⁵
- Zero VOC emissions exceeds CA Specification 01350.

Applications

- Conference and lobby areas
- Department stores
- Entertainment and gaming
- Executive offices
- Restaurants

Substrate

Cast mineral fiber

To order samples, go to usg.com





Sandrift[™] ClimaPlus[™]

To order samples/literature:
Web: usg.com
E-mail: samplit@usg.com
Fax: 888 874.2348
Technical Services:
800 USG.4YOU (800 874.4968)

Websites:
usg.com
usgdesignstudio.com
For the most up-to-date
technical information:
usgdesignstudio.com

(I) UL Classified														
30	Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ²	Color ³	Grid Options	VOC Emissions	Anti-Mold & Mildew	Abuse Resistant	Recycled Content ¹	Panel Cost
Year System Warranty No visible sag Mold/mildew protection			0		0	•	0		•	3	0	4	4	8
Sandrift™ ClimaPlus™ Panels	SL	2'x2'x3/4" Paper-Back	Class A	808	.70	38	.83	White Standard Advantage	А	Zero		4	69% HRC	\$\$\$
	FL	2'x2'x3/4" Paper-Back	Class A	809	.70	38	.83	White Standard Advantage	B, C, D, E	Zero		4	69% HRC	\$\$\$
Sandrift Non- <i>ClimaPlus</i> Panels	SL	2'x2'x3/4" Paper-Back	0	815	.55	35	.83	White	A	Zero		4	69% HRC	\$\$\$
	Legend													
	01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on the CHPS					ClimaPlus Superior Performance ⁴ Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew.				High Recycled Content Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. ≥ .70 NRC Firecode®				
	A DX®/DXL™	B Centricitee™ DXT™	C Fineline® 1/ DXFF™	B Fineline DXF™	e	E Identitee™ DXI™								
Grid Profile Options														

Physical Data/ Footnotes

Product literature Data sheet: SC1841

ASTM E1264 classification

Type III, Form 4, Pattern Z

ASTM E84 surface burning characteristics

Class A Flame spread: 25

Smoke developed: 50

Weight

1.60 lbs./sq. ft. (Class A)

1.75 lbs./sq. ft. (Firecode weight)

Thermal resistance R-1.7 (Class A)

R-1.3 (Firecode)

Maximum backloading

See USG 30-Year Limited Warranty Commercial Applications SC2102.

Maintenance

Can be cleaned easily with a soft brush or vacuum.

Texture

The manufacturing process for cast ceiling panels creates natural, subtle texture variations, which is a distinguishing feature of these products. Because of potential variances between production dates, we recommend ordering and installing cast products by production lot number.

Notes

- For details, see LEED report tool at usgdesignstudio.com.
 LR values are shown as averages.
- To highlight the unique texture of Sandrift *ClimaPlus* panels, choose light colors. See Colors selector for more information.
- more information.

 4. For details, see Ceiling Systems
 Limited Warranty Commercial
 Applications (SC2102) and ClimaPlus
 Ceilings Certification of Performance
 (SC2451)
- (Soc43).

 5. This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

